Product datasheet

Specifications





Symmetra PX Battery Frame for 400V PX 96/160kW & 208V PX 100kW with 9 Battery Modules & Startup

SYCFXR9-9

Overview

Lead Time

Usually Ships within 8 Weeks

Main

Battery Type Provided Equipment

Installation guide User manual

VRLA

Batteries & Runtime

Number Of Battery Blocks Per String	4
Number Of Battery Free Slots	0
Number Of Battery Filled Slots	9
Device Mounting	19 inch battery tray
Additional Information	Request SYBT9-B4 for replacement battery

Physical

_	
Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net Weight	1209 kg
Usb Compatible	No

Conformance

Product Certifications	CE EUROBAT	
Standards	EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 UL 1778	

Environmental

Ambient Air Temperature For Operation	040 °C
Operating Altitude	03333 ft
Relative Humidity	095 %



Ambient Air Temperature For Storage	-1540 °C
Storage Altitude	0.0015240.00 m
Storage Relative Humidity	095 %

Packing Units

-	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	213.4 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	1343 kg

Contractual warranty

Warranty

1 year repair or replace

2



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.



Take-back RoHS/REACh

Resource performance

Take-Back Program Available

Well-being performance

Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
	EU RoHS Declaration

