



Symmetra PX Battery Frame for 400V PX 96/160kW & 208V PX 100kW for 9 Battery Modules & Startup

SYCFXR9-S

Overview

Lead Time Usually Ships within 8 Weeks

Main

Battery Type	VRLA
Provided Equipment	Installation guide

Batteries & Runtime

Number Of Battery Blocks Per String	4
Number Of Battery Free Slots	9
Number Of Battery Filled Slots	0
Device Mounting	19 inch battery tray
Additional Information	Request SVRTQ-R4 for replacement hattery

Physical

Colour	Black
Height	199.1 cm
Width	60 cm
Depth	107 cm
Net Weight	345 kg
Usb Compatible	No

Conformance

Product Certifications	CE
Standards	EN/IEC 62040-2 EN/IEC 62040-3
	EN/IEC 62040-1-1

Environmental

Ambient Air Temperature For Operation	040 °C
Operating Altitude	03333 ft
Relative Humidity	095 %
Ambient Air Temperature For Storage	-1540 °C

Storage Altitude	0.0015240.00 m
Storage Relative Humidity	0. 95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	215 cm
Package 1 Width	121 cm
Package 1 Length	84.8 cm
Package 1 Weight	379 kg

Contractual warranty

Warranty 1 year repair or replace



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Learn more >





Take-back RoHS/REACh

Resource performance



Take-Back Program Available

Well-being performance



Lead Free

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration