

APC Service Bypass Panel- 230V, 32A, MBB, IEC320 C20/HW input, IEC-320 Output- (2) C19 (8) C13

SBP5000RMI2U

Overview

Lead Time Usually in Stock

Main

Mairi	
Main Input Voltage	230 V
Main Output Voltage	230 V
Input Connection Type	IEC 60320 C20
Number Of Rack Unit	2U
Number Of Cables	1
Provided Equipment	Hardwire panel Installation guide Rack mounting brackets User manual Wall mounting brackets

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	66 cm
Net Weight	11.36 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted

Input

Network Frequency	50/60 Hz
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Max Line Current	32 A
Input Current Limits	32 A
Load Capacity	7680 VA
Power Factor	01

Output

Max Current Draw 32 A

Number Of Power Socket Outlets	8 IEC 60320 C13 2 IEC 60320 C19
Protection Type	Circuit breaker
Efficiency	99 %

Conformance

Product Certifications	CSA GOST
Standards	EN/IEC 62040-1:2019/A11:2021
	EN/IEC 62040-2:2006/AC:2006
	EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	-2050 °C
Relative Humidity	095 %
Operating Altitude	015000 ft
Ambient Air Temperature For Storage	-2565 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	20.3 cm
Package 1 Width	61 cm
Package 1 Length	99.1 cm
Package 1 Weight	23.18 kg
Unit Type Of Package 2	PAL
Number Of Units In Package 2	12
Package 2 Height	130.8 cm
Package 2 Width	100 cm
Package 2 Length	120 cm
Package 2 Weight	277.596 kg

Contractual warranty

Warranty 2 years (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

