Specifications



APC Service Bypass Panel- 230V; 32A; MBB; Hardwire input; (4) IEC-320 C19 Output

SBP6KRMI2U

Overview	
Lead Time	Usually in Stock
Main	
Main Input Voltage	230 V
Main Output Voltage	230 V
Number Of Rack Unit	2U
Provided Equipment	Installation guide Rack mounting brackets User manual
Physical	
Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	66 cm
Net Weight	11.36 kg
Mounting Location	Front

Mounting Mode

Mounting Preference

Input		
Network Frequency	50/60 Hz	
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)	
Max Line Current	32 A	
Input Current Limits	32 A	
Load Capacity	7680 VA	
Power Factor	01	

Lower

Rack-mounted

Output

Max Current Draw	32 A
Number Of Power Socket Outlets	4 IEC 60320 C19
Protection Type	Circuit breaker
Efficiency	99 %



Conformance

Product Certifications	CSA GOST
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient Air Temperature For Operation	-2050 °C
Relative Humidity	095 %
Operating Altitude	015000 ft
Ambient Air Temperature For Storage	-4065 °C
Storage Relative Humidity	095 %
Storage Altitude	0.0015240.00 m

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	20.3 cm
Package 1 Width	99.1 cm
Package 1 Length	61 cm
Package 1 Weight	22.72 kg

Contractual warranty

Warranty

2 years (parts only)

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Learn more >

Well-being performance

Mercury Free

Reach Regulation	REACh Declaration
Eu Rohs Directive	Not compliant
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

