



APC Smart-UPS RT Isolation Transformer, 3000VA, 230V In/Out, 1x IEC Jumpers & 1x IEC 60320 C19 outlets

SURT001

Overview	V
----------	---

Presentation	Accessory solutions to tailor the Smart-UPS to meet your specific needs.
Lead time	Usually in Stock

Main

wan	
Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	220 V
Input Connection Type	IEC 60320 C20
Number of rack unit	3U
Number of cables	1
Provided equipment	Installation guide Mounting hardware User manual

Physical

Colour	Black
Height	13 cm
Width	43.2 cm
Depth	66 cm
Net weight	56.82 kg
Mounting location	Front
Mounting preference	Lower
Mounting mode	Rack-mounted with kit
USB compatible	No

Input

Input current limits	16 A
Load capacity	3000 VA
Network frequency	50/60 Hz

Output

Number of power socket outlets
1 IEC Jumpers
1 IEC 60320 C19

Conformance

Product certifications	C-Tick CE
Standards	EN 50091-1 EN 55022 class B EN 55024 EN 60950 EN 61000-3-2

Environmental

Ambient air temperature for operation	040 °C
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-2565 °C
Storage Relative Humidity	095 %
Storage altitude	0.0015240.00 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.7 cm
Package 1 Width	98 cm
Package 1 Length	60.3 cm
Package 1 Weight	63.64 kg
SCC14	10731304217784

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
China RoHS Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty 2 years repair or replace

Recommended replacement(s)