

APC Symmetra RM 8-12kVA Power Module (4kVA)

SYPM4KU

Overview	•
----------	---

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock
Main	
Main Input Voltage	200 V 208 V 230 V
Other Input Voltage	220 V
Main Output Voltage	200 V 208 V 230 V
Other Output Voltage	220 V
Rated power in W	2800 W
Rated power in VA	4000 VA
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	0U
Provided equipment	Installation guide

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0

Physical

•	
Height	15 cm
Width	25 cm
Depth	59 cm
Net weight	15 kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	155276 V

Output

Maximum configurable power in W	2800 W
Harmonic distortion	Less than 3 %
Output frequency	50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest factor	Up to 5 : 1
Wave type	Sine wave

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	43.9 cm
Package 1 Width	79 cm
Package 1 Length	33 cm
Package 1 Weight	18.18 kg

Offer Sustainability

EU RoHS Directive Under investigation

Contractual warranty

Warranty 2 years

Recommended replacement(s)