

# Product datasheet

Specifications



## APC DIN Rail - Panel Mount UPS without Battery-500VA 230V

SUA500PDR1

### Overview

Presentation	Proven Industrial UPS power protection for control applications and harsh environments.
Lead Time	Usually in Stock

### Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	325 W
Rated Power In Va	500 VA
Output Connector Type	Hard wire 3-wire (H N + E) 1
Provided Equipment	CD with software Documentation CD Installation guide Smart UPS signalling RS-232 cable

### Batteries & Runtime

Battery Voltage	24 V
Extended Runtime	0
Battery Capacity	5.0 Ah
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Power In Vah	0 VAh runtime
Replacement Battery	<a href="#">APCRBC135</a> <a href="#">APCRBC136</a>

### General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

### Physical

Height	14.8 cm
Width	36.2 cm
Depth	17.1 cm
Net Weight	8.18 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Input Voltage Limits	151...302 V adjustable 160...285 V
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	500 VA
Maximum Configurable Power In W	325 W
Ups Type	Line interactive
Efficiency	94 % (full load)
Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

## Conformance

Product Certifications	CE VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

## Environmental

Acoustic Level	55 dBA
Heat Dissipation	90 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Ip Degree Of Protection	IP20
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control Panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
---------------	--

---

<b>Emergency Power Off</b>	Yes
----------------------------	-----

---

<b>Free Slots</b>	1
-------------------	---

---

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
--------------	--

## Surge Protection and Filtering

---

<b>Surge Energy Rate</b>	540 J
--------------------------	-------

---

<b>Noise Suppression</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
--------------------------	--

## Packing Units

---

<b>Unit Type Of Package 1</b>	PCE
-------------------------------	-----

---

<b>Number Of Units In Package 1</b>	1
-------------------------------------	---

---

<b>Package 1 Height</b>	29.7 cm
-------------------------	---------

---

<b>Package 1 Width</b>	48.1 cm
------------------------	---------

---

<b>Package 1 Length</b>	29.7 cm
-------------------------	---------

---

<b>Package 1 Weight</b>	9.55 kg
-------------------------	---------

## Contractual warranty

---

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more >](#)



Energy Efficient Take-back Transparency RoHS/REACH

### Resource performance

✓ Energy Efficient Product

---

✓ Take-Back Program Available

---

### Well-being performance

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

### Certifications & Standards

Reach Regulation [REACH Declaration](#)

---

Eu Rohs Directive [Compliant](#)  
[EU RoHS Declaration](#)

---

Environmental Disclosure [Product Environmental Profile](#)

---

Circularity Profile [End of Life Information](#)

---