

Product datasheet

Specifications



UPS Interface Expander 2

AP9624



Overview

Presentation	UPS Management SmartSlot offer with serial shutdown support of up to two additional devices such as Servers and Network Storage Devices.
Lead Time	Usually in Stock

Main

Number Of Cables	2
Provided Equipment	RS-232 configuration cable User manual Warranty card

Physical

Height	3.8 cm
Width	12.1 cm
Depth	11.4 cm
Net Weight	0.07 kg
Mounting Preference	No preference
Mounting Mode	Not rack-mountable

Conformance

Standards	EN 55022 class A EN 55024 FCC part 15 class A IEC 62040-2
Product Certifications	C-Tick CE Industry Canada

Environmental

Ambient Air Temperature For Operation	0...40 °C
Operating Altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Storage Relative Humidity	0...95 %

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.1 cm
Package 1 Width	16.5 cm
Package 1 Length	23.5 cm
Package 1 Weight	0.41 kg

Contractual warranty

Warranty	2 years repair or replace
-----------------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more >](#)



Energy Efficient Take-back RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Lead Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
