Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications



E3SBTH4



Overview	
Presentation	High capacity battery string for use with Easy UPS 3S with internal battery slots and Easy UPS 3S Empty Modular Battery Cabinet (E3SXR6). Each battery string consists of four 9 Ah battery modules (E3SBTHU).
Lead time	Usually Ships within 6 Weeks
Main	
Battery type	VRLA
Batteries & Runtime	
Number of battery free slots	0
Number of battery filled slots	0
Device mounting	Enclosed battery cartridge
Battery voltage	120 V
Battery power in VAh	9 VAh
Physical	
Height	15.7 cm
Width	42.8 cm
Depth	76 cm
Net weight	108 kg
Mounting mode	Not rack-mountable
Environmental	
Ambient air temperature for operation	040 °C
Operating altitude	03281 ft
Relative humidity	095 % non-condensing
Ambient air temperature for storage	-1540 °C
Storage altitude	0.0015240.00 m
Storage Relative Humidity	095 % non-condensing

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	18 cm
Package 1 Width	82 cm
Package 1 Length	56 cm
Package 1 Weight	112 kg

Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Recommended replacement(s)